



# Kingspan TEK® Building System

## SPECIFICATION MANUAL



*Low Energy -  
Low Carbon Buildings*

# Contents

	Page
<hr/>	
Introduction	
Structural Insulated Panel Technology	3
The <i>Kingspan TEK</i> ® Building System	4
Advantages of the <i>Kingspan TEK</i> ® Building System	5
Case Studies	6 – 9
<hr/>	
Design	
Design Flexibility	10
Applications	10
Recommended Constructions	10 – 11
Ventilation	12 – 14
Technical Support	14
Code for Sustainable Homes	15
<hr/>	
Space	
Habitable Roof Space	16
Floor Space	17
<hr/>	
Environmental Sustainability	
Global Issues	18
Local Issues	18
Environmental Sustainability & the <i>Kingspan TEK</i> ® Building System	19
<hr/>	
Energy Efficiency	
General	20
Limited Cold Bridging	21
Air-tightness	21
Roof U-values	23
Service Integration	22
<hr/>	
Internal Linings	23
<hr/>	
Cladding Options	24-25
<hr/>	
Building Process	
Supply and Erect	26
Registered Contractors	26
Joining <i>Kingspan TEK</i> ® Building System Panels	26
Lifting Panels	26
Delivery of the <i>Kingspan TEK</i> ® Building System	26
Storage of Components	26
Alterations to the <i>Kingspan TEK</i> ® Building System	26
Water Ingress During Construction	27
Internal Dry-lining	27
Fixing Items to <i>Kingspan TEK</i> ® Building System Walls	27
Services Installation	27
<hr/>	
Financial Advantages	
Energy Savings	28
Capital Cost Savings	28
Landfill Savings	28
Labour Savings	28
Opens Doors Faster	28
<hr/>	
<i>Kingspan TEK</i> ® Building System Panel Data	
Product Description	29
Product Data	29 – 30
Thermal Properties	30
The Purchasing Process	30



# Introduction



## Structural Insulated Panel Technology

Timber, worldwide, is traditionally the most widely used building material. It is easy to handle, natural and brings flexibility to design.

Today, many buildings are built with a traditional timber frame structure and this trend is growing as Building Regulations / Standards strive for better thermal performance and the construction industry increasingly moves towards the off-site construction of buildings.

Structural Insulated Panel (SIP) technology is the next generation of timber based construction methods.

In the UK and Ireland, demand for off-site construction methods such as SIPs is growing rapidly. This is being driven by factors such as, the availability of on-site skills being at an all time low and the need for organisations such as local authorities and housing associations to innovate when seeking Egan compliance. The introduction of SIPs technology, through systems such as the *Kingspan TEK® Building System* is playing a major role in meeting this demand.

The Code for Sustainable Homes together with the revised Building Regulations / Standards, which came into effect in 2006 in England and Wales and the Republic of Ireland and 2007 in Scotland are demanding much higher levels of energy efficiency. This is challenging many traditional construction systems and, in some instances, forcing people to look at alternative ways of meeting the requirements more economically. Unparalleled energy efficiency combined with high build-speed and the low site wastage make the *Kingspan TEK® Building System* a very cost effective way of achieving compliance with the building fabric measures of the Code for Sustainable Homes and of exceeding the thermal requirement of the Building Regulations / Standards.



# Introduction

## The *Kingspan TEK*® Building System

The *Kingspan TEK*® Building System comprises SIP panels connected with a unique jointing system for walls, roofs and intermediate floors using I-beams or open web joists. Design and structural calculation services are also an integral part of the System.

*Kingspan TEK*® Building System panels consist of a high performance rigid urethane insulation core, with zero Ozone Depletion Potential (ODP), sandwiched between two layers of Oriented Strand Board type 3 (OSB/3). During manufacture, the insulation core of *Kingspan TEK*® Building System panels is autohesively bonded to the OSB/3 facings. This process provides a more reliable and superior adhesion than the traditional secondary bonding process.




*Kingspan TEK*® Building System panels are a structural composite. This composite assembly provides stiffness, strength and predictable responses to applied loads.

The *Kingspan TEK*® Building System is recognised by the major building warranty providers such as Building Life Plans, Homebond, HAPM, NHBC and Zurich Municipal. It also holds BBA, IAB, BM Trada and Zulassung Certification.



The complete System is delivered to site ready for erection by fully qualified *Kingspan TEK*® construction teams. In addition to this, in the UK and Ireland there are a large number of registered *Kingspan TEK*® Building System contractors who will quickly and efficiently erect the System. Details of registered contractors can be downloaded from the website or obtained from the *Kingspan TEK*® Marketing Department (see rear cover).



## Advantages of the *Kingspan TEK*® Building System

### Environmental Sustainability at its Core

- Highly energy efficient.
- U-value range between 0.10 W/m<sup>2</sup>·K and 0.23 W/m<sup>2</sup>·K.
- Air-tight construction – as low as 0.08 air changes per hour at normal air pressures or 0.91 air changes per hour at 50 Pa (approximately 1 m<sup>3</sup>/hour/m<sup>2</sup> at 50 Pa).
- Low site wastage as schemes are designed, cut and palletised in the factory meaning no excess building materials are delivered to site.
- All the components for a typical *Kingspan TEK*® Building System scheme e.g. panels and ancillaries, come from one source, therefore there are fewer deliveries compared to more traditional construction methods where components can often be sourced from and delivered by a number of different distributors or manufacturers. The overall result is less transport, which reduces the project's impact on the environment.
- PEFC Certificated - Chain of Custody.
- Green Guide A+ or A rating depending on cladding.
- Manufactured with a blowing agent that has zero Ozone Depletion Potential (ODP) and low GWP (Global Warming Potential).



### Egan Compliant

- Panelised system enables a fast track building process, which helps to reduce construction time considerably.
- Follow on trades can start work sooner as the *Kingspan TEK*® Building System, when wrapped with a non-tenting breather membrane (e.g. *Kingspan nilvent*®) offers a weather-tight shell helping the contractor complete the project faster.
- For the contractor and developer, faster completion of projects can result in earlier cash recovery, improved cashflow and can increase capacity through the ability to achieve more project completions in a year.
- Much easier to predict project completion times as the System is relatively simple to erect and requires no wet trades or brick layers.
- As a result of reduced time on-site, and as only trained and approved contractors will erect the *Kingspan TEK*® Building System, the likelihood of accidents on-site are reduced.
- Defects are vastly reduced due to the factory controlled manufacture, precise engineering and design of the system.

### Innovative

- More controllable indoor environment than traditional construction methods such as masonry due to the superior air-tightness of the System.
- Incorporates a room in roof, so it is an excellent solution to Planning Policy Statement Note 3 (PPS3) in England and Section 5 in the Planning and Development Act in the Republic of Ireland.
- First SIPs building system in the UK and Ireland to receive BBA and IAB certification.
- **Building Homes Innovation Awards – Runner-up 2001.**
- **Plan Expo Best Innovation Category – Winner 2001.**
- **Plan Expo Best Sustainable Product Category – Highly Commended 2001.**
- **BBA Innovation Award winner 2002.**
- **Design for Manufacturer (60K Competition) – Winner 2006.**
- **Used on the UK's first house to achieve Code for Sustainable Homes – Level 6 (BRE Innovation Centre 2007).**



# Multiple Residential - Private & Social

The *Kingspan TEK*® Building System has been widely used across the UK and Ireland by major developers, house builders and housing associations to construct multiple residential dwellings.



Private Residential - Cleveland



Private and Social - Beswick, Manchester



Private Residential - Nettlesworth



Private Residential - Bay Horse Court, Skipton



Private Residential - Waterloo Mills, Silsden

To these clients the System offers a range of unique advantages, including: speed of construction; predictable completion dates; less on-site labour and the provision of a weather-tight shell.



Private and Social – Broadlands HA, Norfolk



Private Residential – North East



Private and Social – Reema, Petersfield

# Education & Healthcare

Public Sector buildings are increasingly required to meet a standard of construction above and beyond those set out in the Building Regulations. By demanding low U-values and low long term running costs the Public Sector seeks to ensure that the buildings they commission offer not only the best value for money, but also deliver industry best practice in respect of environmental and socio-economic responsibility.



Education – Southwark, London (night view)



Education – Peckham, London



Healthcare – St. Catherine's Hospice, Scarborough



Education – Berkeley School, Gloucestershire



Education – William Penn Nursery, Berkshire

# Private Residential

The *Kingspan TEK*® Building System has long proved popular with those self-builders who demand the best possible construction techniques for their new home. By offering a super insulated structure, with very low fuel bills, additional room space and a quick and predictable build programme the *Kingspan TEK*® Building System meets their exacting standards and is recognised by a range of industry bodies.



Kings House, Oxford (night view)



Middle Barton, Oxfordshire



Kingspan Lighthouse, Watford



Battle, East Sussex



Durham



Clane, County Kildare

# Design

## Design Flexibility

The *Kingspan TEK*® Building System leaves ample scope for individual design. The panels are pre-cut in the manufacturing plant according to individual construction plans. The complete System is delivered to site ready for erection by the fully qualified construction team.

The *Kingspan TEK*® Building System can be used to create the walls (loadbearing and non-loadbearing), roofs and floors of a complete building. Alternatively, roof and wall elements of it can be used individually with other non-*Kingspan TEK*® Building System components. For example the *Kingspan TEK*® Building System can be used as a roofing system in conjunction with masonry or timber frame walls.

The *Kingspan TEK*® Building System can be erected on any flooring system, however the foundations must have specific tolerances as per guidance available from the Kingspan *TEK*® Technical Services Department (see rear cover).



## Applications

The *Kingspan TEK*® Building System can be used to create buildings up to 4 storeys. The panels are lightweight compared to brick and block, at a maximum of 25 kg/m<sup>2</sup>, therefore they are ideal for use, where heavy constructions are not possible.

As with all construction methods, including traditional masonry, a long lasting external weather proofing is also a necessary part of the *Kingspan TEK*® Building System.

NB The System is not recommended for cellars or basement constructions.

If a building guarantee is required e.g. 10 year warranty from Building Life Plans, Homebond, NHBC, Zurich Municipal, then guidance should be sought from the organisation offering the guarantee. Typically, a third party independent certificate would be required e.g. BBA or IAB certificate.

## Recommended Constructions

### Internal / Partition Walls

Internal / partition walls are supplied as kiln dried timber stud components.

Where cabled services are required, it is recommended that they be fixed into a timber or steel stud wall. However, where cabled services need to be fixed to an internal wall that is constructed from *Kingspan TEK*® Building System wall panels there are two options (see Figures 8-10 on page 22):

- single layer of minimum 15 mm plasterboard on minimum 10 mm deep by 38 mm wide vertical timber battens; or
- double layer of minimum 12.5 mm plasterboard – the layer closest to the *Kingspan TEK*® Building System wall panel should be chased out to create a cavity for services. The second layer should be 12.5 mm plasterboard.

Where cabled services do not need to be fixed to the *Kingspan TEK*® Building System wall panel, a single layer of 15 mm sound resisting plasterboard can be fixed direct to the wall panel.

NB Requirements for minimum thickness and number of layers of plasterboard will vary depending on fire rating required.

### External Walls

#### Internal Cladding

All *Kingspan TEK*® Building System wall panels should be lined internally with vapour check plasterboard. Please consult with the Kingspan *TEK*® Technical Services Department (see rear cover) for definitive guidance on your construction.

Where services need to be fixed on an external *Kingspan TEK*® Building System wall, there are two options for creating a service cavity (see Figures 8-10 on page 22):

- single layer of 12.5 mm plasterboard on min. 10 mm deep by 38 mm wide vertical timber battens; or
- double layer of 12.5 mm plasterboard – the layer closest to the *Kingspan TEK*® Building System wall panel should be chased out to create a cavity for services. The second layer should be 12.5 mm vapour check plasterboard.\*

Where cabled services do not need to be fixed to the *Kingspan TEK*® Building System wall panel, a single layer of 12.5 mm vapour check plasterboard\* can be fixed direct to the wall panel.

#### External Cladding

Before cladding *Kingspan TEK*® Building System walls, a non-tenting breather membrane (e.g. *Kingspan nilvent*®) is fixed direct to the wall panels. A minimum cavity of 25 mm should be maintained between the breather membrane and the wall cladding.

The following are wall cladding options for the *Kingspan TEK® Building System* (see Figures 11–16 pages 23–24):

- outer leaf of brickwork / stone, ensuring a minimum 50 mm cavity is maintained between the breather membrane and the brickwork;
- lightweight render coating carried on calcium silicate board which is supported by min. 25 mm deep by 50 mm wide vertical treated timber counter battens;
- feather edge timber boarding on min. 25 mm deep by 50 mm wide vertical treated timber counter battens;
- wall tiling mounted on tiling battens which are supported by min. 25 mm deep by 50 mm wide treated timber counter battens; and
- proprietary brick slip system supported by min. 25 mm deep by 50 mm wide vertical treated timber counter battens;

If other wall cladding options are being considered, contact the Kingspan **TEK®** Technical Services Department.

### Separating Walls (Party Walls)

#### Timber Frame

Robust Standard Details are available but typically, party walls are manufactured from kiln dried timber stud components. Both timber frame wall panels that form the separating wall should be lined internally with (in order of application):

- 19 mm gypsum plank and 12.5 mm vapour check plasterboard\*; or
- 2 x 15 mm sound resisting plasterboard.

### Roofs

#### Internal Cladding

All *Kingspan TEK® Building System* roof panels should be lined internally with vapour check plasterboard\*.

Where services need to be fixed on a *Kingspan TEK® Building System* roof panel, there are two options for creating a service cavity:

- single layer of 12.5 mm vapour check plasterboard\* on min. 10 mm deep by 38 mm wide vertical timber battens; or
- double layer of 12.5 mm plasterboard – the layer closest to the *Kingspan TEK® Building System* roof panel should be chased out to create a cavity for services. The second layer should be 12.5 mm vapour check plasterboard.\*

Where services do not need to be fixed to the *Kingspan TEK® Building System* roof panel, a single layer of 12.5 mm vapour check plasterboard\* can be fixed direct to the roof panel. Please consult with the Kingspan **TEK®** Technical Services Department (see rear cover) for definitive guidance on your construction.

#### External Cladding

Before cladding the *Kingspan TEK® Building System* roofs, a non tenting breather membrane (e.g. *Kingspan nilvent®*) should be fixed direct to the roof panels.



The cladding options available for *Kingspan TEK® Building System* roofs are:

- tiles on tiling battens;
- slates on slate battens; or
- profiled metal sheeting onto horizontal battens.\*\*

All roof cladding options should be supported by 38 mm x 50 mm vertical treated timber counter battens.

If other cladding options are being considered contact the *Kingspan TEK®* Technical Services Department.

The roof cladding option should be decided upon at the earliest opportunity, as loading design values must be calculated when designing your project in the *Kingspan TEK® Building System*.

*\*Calculations in accordance with BS 5250: 2002 (Code of practice for control of condensation in buildings) will determine whether there is a requirement for a vapour control layer with the Kingspan TEK® Building System. However, it is always good practice to install a vapour control layer as buildings have a tendency to alter their psychrometric conditions (relative humidity) through change of use.*

*This can be installed in the conventional manner, using 500 gauge polythene sheet, or by using vapour check plasterboard.*

*Free condensation risk calculations for specific projects are available upon request from the Kingspan TEK® Technical Services Department (see rear cover). These calculations are performed to BS 5250: 2002 (Code of practice for control of condensation in buildings).*

*\*\*The need for battens may be negated with the use of a suitable breathable underlay.*

# Design

## Ventilation

### The Need for Ventilation

The *Kingspan TEK*® Building System can be considerably more air-tight than conventional constructions, achieving air leakage rates as low as 0.08 air changes per hour at normal pressures.

It is widely accepted that healthy buildings require a minimum air leakage rate of 0.5 air changes per hour at normal pressures. This is typically achieved with conventional construction techniques, but may not be achieved with buildings constructed using the *Kingspan TEK*® Building System when both wall and roof panels are combined. Therefore additional ventilation may be a sensible and beneficial addition to a building constructed with the *Kingspan TEK*® Building System.

The Building Regulations / Standards encourage architects and builders to 'Build Tight, Ventilate Right'. This means controlled ventilation. Introducing controlled ventilation is considered good practice in energy efficiency terms.

### Ventilation Options

One method seems to offer the best solution:

#### Mechanical Ventilation (with Heat Recovery) Systems (MVHR).

These systems bring controlled volumes of fresh air into the building and exhaust controlled volumes of moisture laden or stale air to the outside. With the addition of heat recovery, these systems can recover heat from outgoing air to preheat

the incoming air. This heat recovery can provide a large proportion of the heat required to keep a building at comfortable living temperatures.

NB It is the responsibility of the domestic scale mechanical ventilation with heat recovery systems supplier, for the specific sizing of the equipment and the environmental and improved indoor air quality advantages associated with their systems.

The addition of humidity control to the mechanical ventilation system can provide an environment in which dust mites cannot thrive. This may be of benefit to some asthma sufferers.

Another possibility is:

#### Passive Stack Ventilation (PSV) Systems.

Ducts run from 'wet' rooms - kitchens, bathrooms etc. - up to roof terminals. Warm moisture-laden air rises up the ducts as a result the stack effect, requiring no electric fan or power source. These ducts can have humidity controlled vents i.e. they become activated when humidity levels reach a set point.




Figure 1 MVHR System




Figure 2 Passive Stack Ventilation System

Wall or window inlets provide a flow of replacement fresh air into the building as required. In order to provide fresh air in living areas these inlets may need to be placed in dry rooms. These inlets could be humidity controlled, but the building will still need ventilation when these rooms have low humidity and therefore closed vents. Humidity controlled inlets would appear to be counter productive in a building constructed with the **Kingspan TEK® Building System**.

The position of inlets and extract ducts ensure that air always moves from 'dry' rooms to 'wet' rooms, where it is extracted.

*Disadvantages* - the system may need inlets in 'dry' rooms for it to provide adequate ventilation in a very air-tight building. These inlets may have to remain permanently open and thus provide paths for unwanted wind-generated air-leakage. Although desired ventilation could be achieved, there is a risk that undesired over-ventilation could compromise the energy performance of the building through uncontrolled ventilation.

*Advantages* - while heat recovery is not an option, the system operates with no energy use.

#### Positive Input Ventilation (PIV) Systems.

These systems act rather like mechanical extract in reverse. A fan blows air into a property and effectively pressurises the building. In a building with 'normal' levels of air-tightness, this air is forced out through normal air-leakage pathways e.g. cracks, poorly fitting doors and windows etc., taking moisture and air pollutants with it.

In a very air-tight building these pathways may not occur to any useful extent and so extract ventilation ports may have to be provided. As with PSV, the position of inlet ducts and extract ventilation ports ensure that air always moves from 'dry' rooms to 'wet' rooms, where it is extracted. These extract ventilation ports could be humidity controlled, but the building will still need ventilation when these 'wet' rooms have low humidity and therefore closed vents. Humidity controlled inlets would appear to be counter productive in a building constructed with the **Kingspan TEK® Building System**.

*Disadvantages* – the system may need extract ventilation ports in 'wet' rooms for it to provide adequate ventilation in a very air-tight building. These extract ventilation ports may have to remain permanently open and thus provide paths for unwanted air-leakage. Although desired positive input ventilation could be achieved, there is a risk that undesired wind-generated over-ventilation could compromise the energy performance of the building. Why 'Build Tight' to keep energy use down then cut holes in the system to allow uncontrolled ventilation?

*Advantages* - while heat recovery is not an option, some systems claim to preheat input air by gathering solar heat from the batten space under roof tiles. This may reduce running costs.




Figure 3 Positive Input Ventilation System

# Design

## Heating Systems

Buildings constructed using the *Kingspan TEK® Building System* can be cheap to run from the viewpoint of heating bills because they can be so energy efficient.

You can use any conventional heating system but sizing and controls are important. Heating systems can be 'down-sized' considerably as heating demand can be very low or negligible. Controls are important so as to avoid overheating - a normal domestic heating regime could cause a building constructed with the *Kingspan TEK® Building System* to overheat.

The *Kingspan TEK® Building System* can also act as a stimulus to think outside the box with regards to heating systems. What heat is lost through the fabric of the building or through unintentional bulk air movement can be more than compensated for by incidental gains and the introduction of a combined ventilation and heating strategy e.g. the introduction of a small fan coil into a mechanical ventilation with heat recovery (MVHR) unit or the use of small wood burning stove in tandem with a standard MVHR system.




Figure 4 Heating Systems in the *Kingspan TEK® Building System*

## Important Information

Whatever heating system you chose, you should have it engineered to suit the heating demands of the *Kingspan TEK® Building System* rather than traditional construction methods and if possible install a system that is recognised or approved under Appendix Q of SAP 2005.

## Technical Support

The *Kingspan TEK® Building System* comes with a wide range of technical support.

- Typically the *Kingspan TEK® Building System* is supplied and erected under contract. However, if you wish to erect the system yourselves you can use a contractor that is registered to erect the System. A list of trained Registered Contractors is available for download from the website (see rear cover).
- The *Kingspan TEK® Building System* incorporates a comprehensive Design Service. The customer sends fully dimensioned drawings including plans and elevations\* either via email or by post and they will be engineered into a *Kingspan TEK® Building System* scheme to match your design. The scheme will lay out in detail, the way in which the *Kingspan TEK® Building System* panels are to be joined on site to create your building. You will be consulted on all aspects of design throughout this process, and a full itemised quotation will be provided along with the final scheme.
- The *Kingspan TEK® Technical Services Department* can perform a wide variety of relevant calculations including: U-values, SAP, NHER, Home Energy Rating (see rear cover). The department can also offer advice on subjects such as Ventilation, Heating Systems and compliance with The Code for Sustainable Homes.
- Free condensation risk calculations for specific projects are available upon request from the *Kingspan TEK® Technical Services Department* (see rear cover). These calculations are performed to BS 5250: 2002 (Code of practice for control of condensation in buildings).
- Every design is certified by independent Chartered Engineers which includes full drawings and structural calculations.

\* Only drawings in AutoCAD, DWG and DXF can be sent via email

# Code for Sustainable Homes

## What is the Code for Sustainable Homes?


Implemented by the Government in 2007, the Code for Sustainable Homes (CSH) is designed to bring about a step-change in building practice. It aims to achieve this by setting new standards for the key elements of housing design and construction that affect the sustainability credentials of a new home. The Code uses a rating scheme of one to six stars (six being the best rating).

## How Do You Achieve a Code Rating?

The way to reach various levels of the Code has been kept flexible to enable points to be gained using different approaches to house design. However, certain minimum standards have been set at each level for some categories, such as energy efficiency and water use.

When it comes to achieving Code level 3, the house design must be 25% more energy efficient than one built to the 2006 Building Regulations standard.

The energy efficient *Kingspan TEK*® Building System offers a straightforward route to the energy requirements of the Code.



# Space

## Habitable Roof Space

People are driven to demand habitable roof space by various forces including:

- the demands of PPS3 in England and Section 5 of the Planning and Development Act in the Republic of Ireland are calling for higher housing densities and therefore causing reductions in footprint size (these reductions are forcing builders to build up or down to put floor area into houses); and
- the need to fully utilise all of the potential for space to accommodate changing life styles – homeowners want extra space for a home office, guest rooms, children's play rooms etc., or simply a warm storage area in the roof.



The *Kingspan TEK*® Building System is ideally suited to the creation of a room in the roof because the System's roof and wall panels can achieve U-values of as little as 0.18 W/m<sup>2</sup>·K as standard.

*Kingspan TEK*® Building System roof panels are manufactured up to 7.5 m long and with the use of intermediate purlins, any size of roof can be constructed with the System.



## Floor Space

When building a wall to achieve a U-value of  $0.20 \text{ W/m}^2\cdot\text{K}$  using the **Kingspan TEK® Building System**, the structure can be just 223 mm thick. In comparison, a timber frame wall to achieve the same U-value may have to be 390.5 mm thick, (100 mm brick, 50 mm cavity, 12 mm OSB, 215 mm glass fibre quilt between 215 mm studs, 12.5 mm vapour check plasterboard on dabs). A full fill masonry cavity wall to achieve the same U-value will have to have a wall 430 mm thick (100 mm brick, 205 mm rock mineral fibre full fill, 100 mm dense block, 12.5 mm plasterboard on dabs).

This means that the **Kingspan TEK® Building System** provides more floor space for the same external dimensions. Ideal when considering compliance with the housing densities demanded by guidelines such as PPS3 in England and Section 5 of Planning and Development Act in the Republic of Ireland.




Figure 5




Figure 6







Figure 7



**Kingspan TEK® Building System Wall**  
**Wall thickness 223 mm**  
 Floor space, throughout house:  
**144.21 m<sup>2</sup>**



**Timber Frame Wall**  
**Wall thickness 390.5 mm**  
 Floor space, throughout house:  
**133.14 m<sup>2</sup>**



**Masonry Full Fill Cavity Wall**  
**Wall thickness 430 mm**  
 Floor space, throughout house:  
**130.52 m<sup>2</sup>**

**With the Kingspan TEK® Building System, in the example shown above\*, you achieve 11.07 m<sup>2</sup> more useable floor space than a house built with timber frame walls and 13.69 m<sup>2</sup> more useable floor space than a house built with masonry full fill cavity walls of the same external dimensions and U-value ( $0.20 \text{ W/m}^2\cdot\text{K}$ ).**

*\*Extra floor space based on two storeys*

# Environmental Sustainability

## Global Issues

### **Reduce Space Heating Demand and Go Zero ODP**

It is widely recognised that there are four main global environmental sustainability issues: global warming, non-renewable resource depletion, toxic pollution and ozone depletion, and that these global issues far outweigh any local environmental sustainability issues in their need for immediate attention and potential impact from inaction.

Recent studies have shown that the first three issues are essentially one. The extraction and consumption (burning) of fossil fuels is by far the most significant contributor to global warming, non-renewable resource depletion and toxic pollution.

In the UK 60% of fossil fuels are used to heat buildings and half of this is housing. Therefore as far as housing is concerned environmentally sustainability comes down to two main issues: reduce fossil fuel use and specify zero ODP products.

By far the most economical method of reducing fossil fuel use in housing is to reduce space heating demand. The investment for renewable energy sources only becomes convincing once space heating demand is minimised as capital costs are prohibitive to most.

There are two main methods of reducing space-heating demand: reduce heat losses through the building fabric and reduce heat losses from unintentional air-leakage.

The former has been the subject of Building Regulation for 30 years but still has a long way to go before an optimum level is attained. It is estimated that U-values of  $0.10 \text{ W/m}^2\cdot\text{K}$  would be the practical optimum.

Building Regulations / Standards are only starting to attend to the issue of air-leakage, which becomes more significant an effect as U-values are reduced, but it is likely that Building Regulations / Standards will come to focus more on air-tight constructions over the coming years as U-values and energy performance move closer to the optimum.

## Local Issues

### **Reduce Landfill**

The UK construction industry generates at least 70 million tonnes of waste per annum. In addition to this, it is estimated that 13% of materials that go to site never get used and go straight into the waste stream. The key issue here is the land for landfill, which is fast running out. The government is currently dealing with this by imposing increasingly heavy landfill taxes. However, a number of EU countries have already instigated a landfill ban on combustible and recyclable materials.

### **Reduce Transport**

Traditional construction methods often require delivery of components to site from many different manufacturers or distributors. This can often mean numerous deliveries to site increasing congestion, noise and traffic pollution (which is strictly a global issue), but all of which can have a major impact on the environment.



## Environmental Sustainability & the Kingspan TEK® Building System

### Minimum Space Heating, Zero ODP & Low GWP

The Kingspan TEK® Building System can reduce space heating demands not only by achieving U-values of 0.22 W/m<sup>2</sup>·K as standard and down to 0.10 W/m<sup>2</sup>·K with additional insulation but also by achieving air-tightness as low as 0.08 air changes per hour at normal pressures or 0.91 air changes per hour at 50 Pa. Further information on how this performance helps to reduce space-heating demand can be found in Heating Systems on page 14.

The Kingspan TEK® Building System panels are produced in a continuous zero Ozone Depletion Potential (CFC/HCFC-free) process.



**NB The OSB/3 facings of the panels are manufactured from the routine thinnings from managed plantations.**

### Green Guide Rating

The Green Guide ratings for the Kingspan TEK® Building System, as a result of its comparatively low environmental impact, are heavily influenced by the specification of the rainscreen e.g. brickwork for walls or tiles / slates for roofs. Regardless, the system typically achieves an A+ or A rating.

### Minimal Landfill

The Kingspan TEK® Building System is factory manufactured meaning there is minimal site wastage and therefore more efficient use of materials on-site. The minimal levels of site wastage means less landfill which also helps to reduce cost.

### Less Transport

The complete Kingspan TEK® Building System scheme (e.g. panels and ancillaries) comes from one source. Therefore there is less impact on the environment from congestion, noise and traffic pollution because fewer lorries are travelling to and from sites.

### Chain of Custody

The Kingspan TEK® Building System panels have PEFC Chain of Custody certification in accordance with the TUV NORD CERT auditing and certification procedures and is subject to regular surveillance audits.



## Green Guide Specification

### Domestic External Wall Elements

Element Description	Element Number	2008 Green Guide Summary Rating
Brickwork, cement mortar, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806190057	A+
Canadian cedar cladding, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806210064	A+
Pre-treated softwood weatherboarding on timber battens, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806210063	A+
Polymeric render on cement bonded particle-board on timber battens, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806210062	A+
Concrete tiles on timber battens, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806210066	A+
Clay tiles on timber battens, breather membrane, Kingspan TEK® Building System, plasterboard on battens, paint	806210065	A

### Domestic Pitched Roof Elements

Kingspan TEK® Building System, breather membrane, counterbattens, battens and concrete interlocking tiles	812411073	A+
Kingspan TEK® Building System, breather membrane, counterbattens, battens and UK produced fibre cement slates	812411074	A
Kingspan TEK® Building System, breather membrane, counterbattens, battens and UK produced clay plain tiles	812411077	A
Kingspan TEK® Building System, breather membrane, counterbattens, battens and UK produced slates	812411076	A
Kingspan TEK® Building System, breather membrane, counterbattens, battens and resin bonded slates	812411075	A

# Energy Efficiency

## General

The low U-values that can be achieved by using the *Kingspan TEK® Building System* e.g. 0.22 W/m<sup>2</sup>·K with no additional insulation, mean that not only can the System meet and exceed current Building Regulations / Standards but it also can meet the U-values that are expected to be set in future changes to the Building Regulations / Standards in 2012 and beyond. Extremely low U-values e.g. 0.10 W/m<sup>2</sup>·K, can also easily be achieved with the *Kingspan TEK® Building System* by applying additional insulation. This means low running costs and impressive comfort for the lifetime of the building.

In addition to the *Kingspan TEK® Building System* panel's excellent thermal performance, the closed cell structure of its rigid urethane insulation core does not allow movement of air within the wall. The insulation will not sag or physically deteriorate over time as may be the case with other insulating materials.

The proprietary jointing system used with the *Kingspan TEK® Building System* creates a very air-tight structure (as low as 0.08 air changes per hour at normal air pressures) with little opportunity for air leakage.

U-value calculations for a conventional timber framed house always have to take into account, the effects of cold bridging which, in a new build situation is typically 15%. Cold bridging occurs where a material with a significantly worse thermal conductivity interrupts the normal continuous layer of insulation.

The 15% figure includes:

- 38 mm timbers at 600 mm centres for 1 and 2 storey buildings; and
- all timbers such as noggins (also known as repeated cold bridges).

The 15% figure does not include:

- timbers that are outside the wall area used for heat loss calculations;
- timbers (max. depth 50 mm) around window zones and lintels (max. depth 175 mm); and
- intermediate floor joists that are not insulated behind.

The SIP technology, upon which the *Kingspan TEK® Building System* is based, means the insulation layer is not interrupted by repeating studwork. Therefore there is less cold bridging and a better thermal performance. There are however some cold bridges e.g. where timbers are used to support point loads etc. However, as with U-value calculations for timber frame the same rules apply for timbers that do not have to be included.

## Limited Cold Bridging



Due to the continuity of insulation within its panels, the **Kingspan TEK® Building System** provides greatly enhanced thermal reliability when compared with other more traditional forms of construction.

Example 142 mm thick panel.

Thermal bridges exist at:


- 140 mm x 38 mm soleplates where they have been installed on top of the floor screed;
- 50 mm x 110 mm timber headplates;
- half the 50 mm x 110 mm end timbers which are fixed into the wall panels to enable them to be butt jointed at corners;
- half the 50 mm x 110 mm end timbers which are fixed into the roof panels to enable them to be butt jointed over the ridge beam; and
- the 110 mm x 100 mm timbers posts which are occasionally used at the junctions between panels for structural reasons.

This results in a system that only has 4% thermal bridging from timber elements for a typical domestic building wall (up to 15% or more with a traditional timber frame wall) and 1% thermal bridging from timber elements for a typical domestic building roof (6% in a typical domestic roof with insulation between joists or rafters). Guidance on thermal bridging in the **Kingspan TEK® Building System** should be sought from the **Kingspan TEK® Technical Services Department** (see rear cover).

The **Kingspan TEK® Building System** does not suffer from:

- sagging insulation;
- wet insulation due to exposure on site which could reduce thermal performance;
- gaps and voids in insulation coverage left by poor site workmanship; or
- compressed loft insulation from storage of items in the loft.

## Air-tightness



The **Kingspan TEK® Building System** is ideal for the construction of an air-tight building envelope. The System's proprietary jointing system provides an effective air seal.

The **Kingspan TEK® Building System** does not suffer from the problems associated with other common construction techniques:

- air leakage through poorly sealed sockets, switches etc. in timber frame walls;
- air leakage at floor zones through wet plastered masonry cavity walls;
- air leakage under skirting boards and through poorly sealed sockets, switches etc. in dry lined masonry cavity walls; and
- air leakage through poorly sealed loft hatches and top storey ceiling light fittings.

The **Kingspan TEK® Building System** achieves excellent results in blower door tests e.g. 0.08 air changes per hour at normal air pressures or 0.91 air changes per hour at 50 Pa (approximately 1 m<sup>3</sup>/hr/m<sup>2</sup> at 50 Pa).

# Service Integration / Internal Linings




Figure 8  
Minimum 12.5 mm vapour check\* plasterboard on 25 mm timber battens†.




Figure 9  
Minimum 12.5 mm vapour check\* plasterboard on 19 mm gypsum Plank or 12.5 mm plaster board.




Figure 10  
Minimum 12.5 mm vapour check\* plasterboard fixed direct to the Kingspan TEK® Building System.

The minimum plasterboard requirement may vary subject to statutory requirements for fire and acoustics.

The need for electrical sheathing / conduit should be assessed in accordance with Building Regulations / Standards and BS 7671: 2001

# Typical Wall Constructions




Figure 11  
12.5 mm vapour check\* plasterboard on 25 mm timber battens<sup>†</sup>.  
Non tenting breather membrane (e.g. Kingspan nilvent®, 50 mm cavity, brickwork facing. U-value 0.19 - 0.21 W/m<sup>2</sup>·K.




Figure 12  
12.5 mm vapour check\* plasterboard on 25 mm timber battens<sup>†</sup>.  
Non tenting breather membrane (e.g. Kingspan nilvent®, 25 mm (min.) vertical treated timber counter battens, calcium silicate board with lightweight render coating. U-value 0.20 - 0.22 W/m<sup>2</sup>·K.




Figure 13  
12.5 mm vapour check\* plasterboard on 25 mm timber battens<sup>†</sup>.  
Non tenting breather membrane (e.g. Kingspan nilvent®, 25 mm (min.) vertical treated timber counter battens, proprietary brick slip system. U-value 0.20 - 0.22 W/m<sup>2</sup>·K.




Figure 14  
Kingspan Kooltherm® K18 Insulated Plasterboard.  
Non tenting breather membrane (e.g. Kingspan nilvent®, 25 mm (min.) vertical treated timber counter battens, calcium silicate board with lightweight render coating.

# Cladding Options




Figure 15  
12.5 mm vapour check\* plasterboard on 25 mm timber battens†.  
Non tenting breather membrane (e.g. **Kingspan nilvent®**, 25 mm (min.) vertical treated timber counter battens, timber boarding. U-value 0.20 - 0.22 W/m<sup>2</sup>·K.






Figure 16  
12.5 mm vapour check\* plasterboard on 25 mm timber battens†.  
Non tenting breather membrane (e.g. **Kingspan nilvent®**, 25 mm (min.) vertical treated timber counter battens, tiling battens, tile hanging. U-value 0.20 - 0.22 W/m<sup>2</sup>·K.

## Wall U-values

- Using the **Kingspan TEK®** Building System complete walls can easily provide extremely low U-values between 0.10 W/m<sup>2</sup>·K and 0.22 W/m<sup>2</sup>·K.
- The **Kingspan TEK®** Building System is clearly bringing future building standards home today.



**Figure 17**  
12.5 mm vapour check\* plasterboard on 25 mm timber battens†.  
Non tenting breather membrane (e.g. **Kingspan nilvent®**), 38 mm x 38 mm vertical treated timber counter battens, tiling battens and tiles / slates. U-value 0.18 - 0.20 W/m<sup>2</sup>·K.



**Figure 18**  
37.5 mm **Kingspan Kooltherm®** K18 Insulated Plasterboard.  
Non tenting breather membrane (e.g. **Kingspan nilvent®**), 38 mm x 38 mm vertical treated timber counter battens, tiling battens and tiles / slates. U-value 0.16 W/m<sup>2</sup>·K.

† An alternative to plasterboard on battens is two layers of 12.5 mm plasterboard with the inner layer being vapour check plasterboard\*.

\*Calculations in accordance with BS 5250: 1989 (1995) (Code of practice for control of condensation in buildings) will determine whether there is a requirement for a vapour control layer with the **Kingspan TEK®** Building System. However it is always good practice to install a vapour control layer as buildings have a tendency to alter their psychrometric conditions (relative humidity) through change of use. This can be installed in the conventional manner, using 500 gauge polythene sheet, or by using vapour check plasterboard.

## Roof U-values


Using the **Kingspan TEK®** Building System complete roofs can easily provide extremely low U-values.

For roofs in dwellings with insulation in the slope of the roof (room in roof constructions) 0.20 – 0.16 W/m<sup>2</sup>·K are the current U-values required by the Building Regulations / Standards in the UK and Ireland.

**Kingspan TEK®** Building System can clearly meet these requirements.

All U-values stated for the **Kingspan TEK®** Building System are quoted for a complete element build up consisting of all layers involved in the detail, including the external and internal surface resistances and does not relate to the **Kingspan TEK®** Building System panel on its own.

It is always advisable to undertake a condensation risk analysis in accordance with BS 5250: 2002 as the same time as performing the U-value. This will evaluate the likelihood of interstitial condensation.



# Building Process

## Supply and Erect

Typically, the complete System is delivered to site ready for erection by fully qualified construction teams.

## Registered Contractors

In addition, *Kingspan TEK*<sup>®</sup> has a network of Registered *Kingspan TEK*<sup>®</sup> Building System Contractors throughout UK and Ireland. Contact *Kingspan TEK*<sup>®</sup> Customer Services (see rear cover) for more information. These contractors, who have a background of timber frame, SIPs, green oak framing as well as traditional masonry construction have undergone special training to erect the *Kingspan TEK*<sup>®</sup> Building System.

The services offered by registered contractors range from simple erection of the *Kingspan TEK*<sup>®</sup> Building System through to a full turn key package including the provision heating and ventilation equipment, windows, doors, staircases and all external finishes.



## Joining *Kingspan TEK*<sup>®</sup> Building System Panels

*Kingspan TEK*<sup>®</sup> Building System panels have a routed channel along their long edges, which accommodate a unique cassette joint. These are fixed through the panel's OSB/3 facings.

Expanding urethane sealant is applied between the urethane core of the cassette and the panel. Sealing this jointing system with the expanding urethane sealant enables the *Kingspan TEK*<sup>®</sup> Building System to be very air-tight.



## Lifting Panels

*Kingspan TEK*<sup>®</sup> Building System panels should only be lifted by fully qualified construction teams or Registered Contractors who have completed the *Kingspan TEK*<sup>®</sup> Building System training course. Lifting should be organised in accordance with the Registered Contractors own method statement.

## Delivery of the *Kingspan TEK*<sup>®</sup> Building System

Information relating to the site and its access will be required and should be provided at an early stage e.g. quotation stage. When the *Kingspan TEK*<sup>®</sup> Building System is delivered, it will be via an appropriate sized vehicle.

Additional information relating to the unloading, use and positioning of a crane and other machinery should be discussed with the registered *Kingspan TEK*<sup>®</sup> Building System contractor.

## Storage of Components

*Kingspan TEK*<sup>®</sup> Building System panels should be kept at least 150 mm off the ground on supports, and protected from the elements with a polythene sheet until used. Supports should be supplied at maximum 1,200 mm centres ensuring the ground is flat, so that the panels will not twist.

OSB/3 floorboards should be stacked flat, clear of the floor, on level bearers and at centres not exceeding 600 mm. The whole stack should be covered with a polythene sheet to prevent warping.

## Alterations to the *Kingspan TEK*<sup>®</sup> Building System

Alterations can usually be accommodated during the construction process if required. Prior approval in writing from *Kingspan TEK*<sup>®</sup> will be required. Alterations following completion of the building are possible but more difficult and should, where possible, be carried out by a registered *Kingspan TEK*<sup>®</sup> Building System contractor who has access to the original design plans.

NB A structural engineer must verify all alterations.

## Water Ingress During Construction

*Kingspan TEK*® Building System wall and roof panels are supplied so that they are protected from the elements during and after the construction process. A breathable membrane (e.g. *Kingspan nilvent*®) is factory applied to prevent site error.

## Internal Dry-lining

Plasterboard should be fixed directly to the *Kingspan TEK*® Building System panel. Refer to the *Kingspan TEK*® Building System Construction Manual for full details.

Where services need to be run on a *Kingspan TEK*® Building System wall panel there are alternative internal dry-lining options which are discussed in the Services Installation section on page 28.

## Fixing Items to *Kingspan TEK*® Building System Walls

### Cabinets

Cabinets can be fixed anywhere along the surface of *Kingspan TEK*® Building System wall panels using suitable screw fixings. For optimal strength, cabinets should be hung before the wall panels have been lined with plasterboard. For further information refer to the *Kingspan TEK*® Building System Construction Manual.

### Boilers / Radiators

Boilers / radiators can be fixed anywhere along the surface of an external *Kingspan TEK*® Building System wall using appropriately sized fixings. For further information contact *Kingspan TEK*® Technical Services Department (see rear cover).

### Flexibility of Layout

Compared with timber frame walls where, in many cases, noggins have to be installed to take the load, *Kingspan TEK*® Building System wall panels offer flexibility for layout and the potential for saving time as the need for installing noggins is eradicated\*.

*\*Except in cases where a single layer of plasterboard is mounted on vertical timber battens. In this situation, additional timber battens would need to be fixed as noggins to help take the load off items such as cabinets.*

## Services Installation

### Wiring

Where possible run wiring through internal stud partition walls. However, if it is necessary to run wiring on *Kingspan TEK*® Building System walls there are two possible methods, double layer plasterboard or single layer plasterboard on battens. With both methods ensure that the wiring is protected with an IEE approved metal guard.

Double layer plasterboard is an excellent option, especially if you are building to sell on or rent. Because there is no service cavity, *Kingspan TEK*® Building System walls have a very solid sound unlike timber frame walls.

### Plumbing

Plumbing is done in a conventional fashion, utilising interior partition walls and / or plumbing chases. Any small bore plumbing that must run on a *Kingspan TEK*® Building System wall should be surface mounted using pipe clips screwed through internal lining into the internal OSB/3 facing of the *Kingspan TEK*® Building System wall panels.



# Financial Advantages

## Energy Savings

The thermal efficiency of the *Kingspan TEK® Building System* can offer dramatic energy cost savings over the lifetime of the building.

## Capital Cost Savings

To achieve equal energy performance e.g. a U-value of 0.22 W/m<sup>2</sup>·K and air leakage as low as 0.08 air changes per hour at normal air pressures, the capital cost of the *Kingspan TEK® Building System* would be considerably lower than an equivalent building using timber frame or masonry construction.

## Landfill Savings

The *Kingspan TEK® Building System* arrives on site as a complete scheme therefore there should be no site wastage apart from packaging materials and empty foam cans. This results in more efficient use of materials and also lower landfill fees.

## Labour Savings

The *Kingspan TEK® Building System* is designed and manufactured in the factory. Therefore, the scheme (including all ancillaries and fixings) is delivered complete and from one source, which will enable a weather-tight structure to be erected quickly.

Easily recognised components are shipped to the site for assembly, rather than waiting for a builder's interpretation of plans. *Kingspan TEK® Building System* panels also come in much larger dimensional sizes than other building materials meaning fewer components have to be handled during the erection process. A registered contractor's team of 4-6 can erect a *Kingspan TEK® Building System* very quickly.

This can compare favourably with traditional construction techniques such as brick and block where there are more components which can result in more processes and therefore more labour and possible construction errors.

## Opens Doors Faster

When the building is built for the purpose of renting, the shorter construction time of the *Kingspan TEK® Building System*, can enable tenants to move in sooner and consequently the owner achieves a better cash flow and therefore faster payback.

# Kingspan TEK® Building System Panel Data

## Product Description

### The Facings

*Kingspan TEK®* Building System panels are faced on both sides with a maximum of 15 mm OSB/3, autohesively bonded to the rigid thermoset urethane insulation core during manufacture.

### The Core

The core of *Kingspan TEK®* Building System panels is a high performance CFC/HCFC-free rigid thermoset urethane insulant of typical density 33 kg/m<sup>3</sup>, manufactured with a blowing agent that has zero Ozone Depletion Potential (ODP).



### Green Guide Rating

The Green Guide ratings for the *Kingspan TEK®* Building System, as a result of its comparatively low environmental impact, are heavily influenced by the specification of the rainscreen e.g. brickwork for walls or tiles / slates for roofs. However, the system typically achieves an A+ or A rating.

## Product Data

### Standards and Approvals

*Kingspan TEK®* Building System panels are manufactured to the highest standards under a documented internal factory production quality control management system. The *Kingspan TEK®* Building System's use is covered by BBA certificate 02/S029, IAB certificate 02/0158 and Zulassung certificate 2-9.1-315.



### Chain of Custody

The *Kingspan TEK®* Building System panels have PEFC Chain of Custody certification in accordance with the TUV NORD CERT auditing and certification procedures and is subject to regular surveillance audits.



The OSB/3 facings used in the manufacture of *Kingspan TEK®* Building System panels have BM TRADA Q-Mark product certification.

Q-Mark is the ideal tool for independently proving that products are:

- properly tested and appraised in the first instance;
- manufactured under an appropriate quality management system; and
- consistently manufactured to the same high standard, day after day.



### Structural Insulated Panel Standard Dimensions

Width: 200 mm (min.) – 1220 mm (max.)

Length: 7,500 mm (max.) – for walls a maximum 3 m storey height is allowed.

### Water Vapour Resistance

Vapour resistance of *Kingspan TEK®* Building System panel components:

- the rigid urethane core – 33.6 MN.s/g; and
- the OSB/3 facing – 7.5 MN.s/g.

### Durability

The *Kingspan TEK®* Building System panels will have comparable durability to that of OSB/3 to BS EN 300 (Code of Practice for the selection and application of Particle Board, Oriented Strand Board (OSB), Cement Bonded Particle Board and Wood Fibre for specific purposes.), therefore as long as the System remains weather-tight, a life of at least 60 years may be expected.

### Resistance to Solvents, Fungi and Rodents

The rigid urethane insulation core is resistant to dilute acids, alkalis, mineral oil and petrol. It is not resistant to some solvent-based adhesive systems, particularly those containing methyl ethyl ketone.

Adhesives containing such solvents should not be used in association with *Kingspan TEK®* Building System. *Kingspan TEK®* Building System components, which have been in contact with harsh solvents, petrol, mineral oil or acids, or components that have been damaged in any way should not be used.

The rigid urethane insulation core and facings used in the manufacture of *Kingspan TEK®* Building System panels resist attack by mould and microbial growth and do not provide any food value to vermin.

### Fire Performance

The *Kingspan TEK®* Building System exceeds the Building Regulations / Standards requirements with regards to fire resistance. When tested in accordance with BS 476: Part 21: 1987 (Fire tests on building materials and structures. Methods for determination of the fire resistance of load bearing elements of construction to the Building Regulations / Standards) achieved up to 73 minutes resistance.

NB Requirements for minimum thickness and number of plasterboards will vary depending on fire rating required.

# Kingspan TEK® Building System Panel Data

## Resistance to Airborne Sound

Field tests to BS EN ISO 140-4: 1998 (Field measurements of airborne sound insulation between rooms) on separating walls, externally faced with 12.5 mm plasterboard, 19 mm gypsum planks and 9.5 mm plasterboard to each *Kingspan TEK® Building System* wall panel, achieved an average sound reduction of 58 dB ( $D_{nT,w}$  (C;C<sub>tr</sub>) 58 (-3; -7) dB).

A laboratory test on a single wall panel with no internal dry-lining achieved a sound reduction (R<sub>w</sub>) of 31 dB.

When adopting the use of super dried timber frame party walls, the guidelines contained within the Robust Standard Details would be followed.

## Thermal Properties

The  $\lambda$ -values and R-values quoted are based on accelerated ageing for 25 weeks at 70°C, in line with the methods used in the new European Standard BS EN 13165: 2001 (Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products – Specification). Comparison with alternative products may not be appropriate unless the same procedures have been followed.

### Thermal Conductivity

Thermal conductivity ( $\lambda$ -value) of the OSB/3 component of *Kingspan TEK® Building System* panels should be taken as 0.13 W/m.K. The thermal conductivity of the insulation core of *Kingspan TEK® Building System* panels is 0.023 W/m.K.

### Thermal Resistance

*Kingspan TEK® Building System* panels have a thermal resistance (R-value) at a maximum of 5.100 m<sup>2</sup>.K/W. It is calculated by dividing the thickness of each component (expressed in metres) by its thermal conductivity and adding the resultant figures together.

## The Purchasing Process

### 10 Steps to **TEK®**

- At the earliest opportunity (e.g. from planning permission) fully dimensioned drawings should be sent to the *Kingspan TEK® Building System* design office.
- *Kingspan TEK®* will confirm receipt of the drawings and allocate the project a project number.
- *Kingspan TEK®* will issue a budget quotation normally within two weeks.
- *Kingspan TEK®* will discuss specific project details and any value engineering requirements with you. A revised quotation will be produced if necessary.
- A written order will be given to *Kingspan TEK®*.
- *Kingspan TEK®* will prepare and generate CAD working drawings.
- CAD drawings are issued for approval and signing by you, usually within four working weeks.
- A delivery date is allocated. This is normally upto six weeks from receipt of signed and approved drawings.
- Typically the *Kingspan TEK® Building System* is supplied and erected under contract. However, if you wish to erect the system yourselves you can use a contractor that is registered to erect the System. *Kingspan TEK®* will provide a list of trained Registered Contractors which is available for download from the website.
- A *Kingspan TEK®* representative will make periodic checks on your project to monitor the erection progress as required.



# Contact Details

## Customer Service

For quotations, order placement and details of despatches please contact the Kingspan **TEK**® Customer Service Department on the numbers below:

UK – Tel: +44 (0) 1544 388 601  
– Fax: +44 (0) 1544 388 888  
– email: customerservice.uk@tek.kingspan.com

Ireland – Lo-Call: 1890 222 555  
– Fax: +353 (0) 47 84 397  
– email: info.ie@tek.kingspan.com

## Literature & Samples

Kingspan produces a comprehensive range of technical literature for specifiers, contractors, stockists and end users.

The literature contains clear 'user friendly' advice on typical design; design considerations; thermal properties; sitework and product data.

Kingspan **TEK**® technical literature is an essential specification tool. For copies please contact the Kingspan **TEK**® Marketing Department on the numbers below:

UK – Tel: +44 (0) 1544 387 384  
– Fax: +44 (0) 1544 387 484  
– email: literature.uk@tek.kingspan.com

Ireland – Lo-Call: 1890 222 555  
– Fax: +353 (0) 47 84 397  
– email: info.ie@tek.kingspan.com

## Technical Advice / Design

Kingspan supports all of its products with a comprehensive Technical Advisory Service for specifiers, stockists and contractors.

This includes a computer-aided service designed to give fast, accurate technical advice. Simply phone the Kingspan **TEK**® Technical Service Department with your project specification. Calculations can be carried out to provide U-values, condensation / dew point risk, required insulation thicknesses etc... Thereafter any number of permutations can be provided to help you achieve your desired targets.

The Kingspan **TEK**® Technical Service Department can also give general application advice and advice on design detailing and fixing etc... Site surveys are also undertaken as appropriate.

Please contact the Kingspan **TEK**® Technical Service Department on the numbers below:

UK – Tel: +44 (0) 1544 387 382  
– Fax: +44 (0) 1544 387 482  
– email: technical.uk@tek.kingspan.com

Ireland – Lo-Call: 1890 222 555  
– Fax: +353 (0) 47 84 397  
– email: technical.ie@tek.kingspan.com

## General Enquiries

For all other enquiries contact Kingspan on the numbers below:

UK – Tel: +44 (0) 1544 388 601  
– Fax: +44 (0) 1544 388 888  
– email: info.uk@tek.kingspan.com

Ireland – Lo-Call: 1890 222 555  
– Fax: +353 (0) 47 84 397  
– email: info.ie@tek.kingspan.com

*Kingspan reserves the right to amend product specifications without prior notice. The information, technical details and fixing instructions etc. included in this literature are given in good faith and apply to uses described. Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan offers a Technical Advisory Service (see above) the advice of which should be sought for uses of Kingspan products that are not specifically described herein. Please check that your copy of the literature is current by contacting the Kingspan **TEK**® Marketing Department (see left).*



TEK

Kingspan Insulation Limited, Pembridge, Leominster, Herefordshire HR6 9LA, UK  
Kingspan Century Limited, Clones Road, Monaghan, County Monaghan, Ireland

[www.tek.kingspan.com](http://www.tek.kingspan.com)

© Kingspan, Kooltherm, nilvent, TEK, the TEK Device, the House Device, the zo Device and the Lion Device are Registered Trademarks of the Kingspan Group plc

Kingspan Insulation Ltd. Registered in England & Wales, No. 01882722. VAT GB428602456.

Registered Office: Pembridge, Leominster, Herefordshire HR6 9LA, UK.

Kingspan Century Ltd. Registered in Ireland, No. 152775. VAT IE6550175J

Registered Office: Dublin Road, Kingscourt, Co. Cavan, Ireland.

Kingspan **TEK**® Delivery Partner

